



Arados de Cohecho



Calidad rentable



Desde 1954



Fondo de estampación, con punta reversible, reja, vertedera y cubrerastrojo.

Body with share point, mouldboard, and coverboards.

Corps avec point, soc, versoir, défecteurs et contre-plaque.



Placa de empalme.

Splicing plate.

Plaque d'enture.



Cierre hidráulico.

Hydraulic locking device.

Fermeture hydraulique.



Gran desahogo.

Clear plough.

Sans bourrage.

Ruedas de control.

Control wheels.

Roues de contrôle.

CARACTERÍSTICAS TÉCNICAS

TECHNICAL CHARACTERISTICS / CARACTERISTIQUES TECHNIQUES



ACH-7B



ACHL-7B

MODELO MODEL MODÈLE	Nº BRAZOS TINES No. Nº BRAS	ANCHO LABOR WORKING WIDTH LARGEUR TRAVAIL	RUEDAS WHEELS ROUES	POTENCIA (C.V.) POWER (H.P.) PUISSANCE (C.V.)
ACH-4B	4	1,28 m.	1	60
ACH-5B	5	1,60 m.	1	75
ACH-6B	6	1,92 m.	1	90
ACH-7B	7	2,24 m.	1	105
ACH-8B	8	2,56 m.	2	120
ACH-9B	9	2,88 m.	2	135
ACH-10B	10	3,20 m.	2	150
ACH-11B	11	3,52 m.	2	170
ACH-12B	12	3,84 m.	2	190
ACH-13B	13	4,16 m.	2	210
ACH-14B	14	4,48 m.	2	230
ACHL-4B	4	1,36 m.	1	70
ACHL-5B	5	1,70 m.	1	85
ACHL-6B	6	2,04 m.	1	100
ACHL-7B	7	2,38 m.	1	115
ACHL-8B	8	2,72 m.	2	130
ACHL-9B	9	3,06 m.	2	145
ACHL-10B	10	3,40 m.	2	160
ACHL-11B	11	3,74 m.	2	175
ACHL-12B	12	4,08 m.	2	190
ACHL-13B	13	4,42 m.	2	220
ACHL-14B	14	4,76 m.	2	250

*El fabricante se reserva el derecho de introducir variantes sin previo aviso.
We reserve the right to introduce modifications without previous warning.
Nous reservons le droit d'introduire des modifications sans avis préalable.*

DISTRIBIDOR OFICIAL
DEALER / VENDEUR :



Desde 1954

Julio Gil Águeda e Hijos, S.A.
Ctra. M-118, km 4,1

28814 Daganzo de Arriba (MADRID)
Tel.: (+34) 91 884 54 29/ 91 884 54 49
Fax: (+34) 91 884 14 87
e-mail: ventas@sembradorasgil.com